

**PureCoat<sup>®</sup>**  
*Premium*

PURE COATING PERFORMANCE

# CementBond

## CEMENT MODIFIER



Ideally used for



FLOOR TILE



BARE CEMENT



TEXTURED FINISH

- ✓ Waterproofing flexible coating
- ✓ Provides superior water resistance, adhesion and durability
- ✓ Eliminates plastering defects, water seepage and bridges hairline cracks

from the makers of  paints



## CementBond CEMENT MODIFIER

A waterproofing flexible coating based on aqueous high grade acrylic polymer designed to be mixed with Portland cement.

The resulting mixture provides superior water resistance, adhesion and durability not found on unmodified cement slurry. It eliminates plastering defects, water seepage and bridges hairline cracks, making it ideal for waterproofing roof decks, firewalls, concrete gutters and basements. It can also serve as textured finish, tile adhesive grouting and concrete restoration floor patching.

### APPLICATION

#### METHOD OF APPLICATION

brush or roller

#### PAINTING SYSTEM

Mix cement mixture of 4 kg of cement to 4 liters of PureCoat Premium CementBond Cement Modifier. Apply mixture on a pre-wetted surface using brush or roller. Apply 3 coats for vertical surfaces and 5 coats for horizontal surfaces. Allow 2 hours interval in between coats. Let it cure for at least 3 days before painting PureCoat Premium Latex Masonry System or PureCoat Premium Duratex System.

#### SURFACE PREPARATION

For maximum paint performance, surfaces to be painted must be dry and in sound condition, free from loose dirt, dust, oil, grease and other foreign matter. These conditions must be ensured before starting paint application.

#### TECHNICAL SPECIFICATION

<b>Appearance</b>	: milky liquid
<b>Viscosity</b>	: 16-20 seconds FC #4 at 28 °C
<b>Theoretical Density</b>	: 1.24 ± 0.02 kg/liter
<b>Theoretical NVM by Weight</b>	: 56%
<b>Theoretical Coverage</b>	: 5-6 sqm/4 liter of cement mixture for waterproofing and textured finish system

#### HEALTH & SAFETY INFORMATION

Keep container tightly closed. **Keep out of reach of children.** Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in well-ventilated area. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/ eye protection/ face protection. Avoid release to the environment.

See SDS for further details & information.



**Sycwin Coating & Wires, Inc.**

93 Joy St., Grace Village, Balingasa, Quezon City 1115 Philippines  
Tel: (632) 8364-8001 to 06, 8364-5790; 3411-3491 to 93 • Fax: (632) 8364-3870  
Email: hello@sycwin.com • Web: www.sycwin.com • Facebook: sycwinpaints