

ALL PURPOSE - FLEXIBLE
WEATHERGARD

Premium Odourless Elastomeric Paint

100% Waterproof

ELASTOMERIC PUTTY

Repairs minor cracks, dents,
scratches while maintaining
its elastomeric property.



Weathergard Elastomeric Putty is an acrylic water-based elastomeric putty especially designed to repair minor cracks, dents, scratches and other surface imperfections on concrete and masonry surfaces prior to painting. Intended for Weathergard Elastomeric Paint for exterior and interior application whenever a smooth finish is desired.

PHYSICAL PROPERTIES

Grind	: 3-4 NS
Package Viscosity:	130,000-150,000 Centipoises @ 28°C
Density	: 1.58 ± 0.02 kg./liter
% Non Volatile	: By weight - 64.78 %
	: By volume - 44.77 %
Appearance	: Flat
Packaging	: 4 Liters

TECHNICAL INFORMATION

Reduction : Use as is, if necessary reduce sparingly with clean water.

Application : Apply 1st coat Weathergard Elastomeric Paint on properly prepare concrete and masonry surface. Let it dry and repair all minor surface imperfection with Weathergard Elastomeric Putty using Palette or Putty knife. When thoroughly dry, sand to a smooth finish before the application of 2 or more coats of Weathergard Elastomeric Paint.

Drying Time :	To touch	- ½ -1 hour
	: Tack Free	- 1-2 hours
	: Hard	- 2-4 hours

SURFACE PREPARATION


For maximum paint performance, surface to be painted must be dry and in sound condition, free from loose dirt, dust, oil, grease and other foreign matter.

In new concrete walls,
to prevent efflorescence
use Elastomeric
Alkali Resistant
Concrete
Sealer



Sycwin Coating & Wires, Inc.

93 Joy St., Grace Village, Balingasa, Quezon City 1115 Philippines
Tel: (632) 3646001 to 06; 3645790; 4113491 to 93 • Fax: (632) 3643870
Email address: sales@sycwin.com • Web: www.sycwin.com

 Like us at www.facebook.com/sycwinpaints

PB-WEP Rev. 1 April 21, 2016