

Left Wall Laguna White 19-101-W Right Wall Silver Gray 19-850-W



Left Wall Tile Red 19-370-W Right Wall Bleached Lime 19-233-W



Walls Soft Green 19-613-W Trim Mustard 19-610-W



Left Wall Sweet Mocha 19-280-W Right Wall Duchess 19-345-W



Left Wall Mint Green 19-684-W Right Wall Lemon Drop 19-226-W



Walls Faraway Blue 19-714-W Trim Grape Jewel 19-784-W

Colors may slightly vary from the actual color chips shown.



# YOUR GUARD FOR ANY WEATHER

### WEATHERGARD Odorless Elastomeric Paint

An odorless elastic acrylic polymer, water based coating intended for exterior and interior masonry surfaces whenever a flexible and durable water proofing finish is desired. It prevents minor water leakage problems due to its excellent adhesion and elongation properties that can withstand hairline cracks caused by expansion and contraction of concrete surfaces due to extreme weather condition prevalent in tropical localities.

#### APPLICATION

Stir well before using. Apply at package consistency. If necessary, use a maximum reduction of ¼-liter clean water per 4-liter paint. Apply 3-4 coats or until film thickness is achieved. Allow 3-4 hours drying time in between coats. Appearance is satin-finish and covers 20-25 sqm / 4-liter paint at 50 microns film thickness (approx 2-3 coats). Apply only during dry and fair weather condition.

To attain a semi-gloss finish, mix 1-liter WeatherGard Odorless Elastomeric Gloss Plus with 4-liters WeatherGard Odorless Elastomeric Paint. Do not add more than the recommended quantity of WeatherGard Odorless Elastomeric Gloss Plus due to slight reduction in

For newly cured high alkaline concrete and very rush painting works, WeatherGard Odorless Elastomeric Alkali Resistant Sealer is used as primer sealer to seal surface against water penetration and salt migration into concrete surface.

To repair minor cracks, dents, scratches and other surface imperfections, use WeatherGard Odorless Elastomeric Putty.

#### SURFACE PREPARATION

For maximum paint performance, surface to be painted must be dry and in sound condition, free from loose dirt, dust, oil, grease and other foreign matter. New concrete must be treated with Purecoat Premium Concrete Neutralizer to reduce excess alkalinity. For repairing old masonry, remove old loose paint, use steel wool or steel brush. Sand down to an even surface to promote adhesion. Repair cracks and dents with proper patching material.

#### **HAZARD STATEMENTS:**

Inhalation of vapors or mist may cause irritation of respiratory system. Causes mild skin and eye irritation.



#### PRECAUTIONARY MEASURES:

Keep out of reach of children. Do not breathe in dust, fume, gas, mist, vapors or spray. Avoid skin contact. Do not eat, drink or smoke when using this product. Wear protective gloves & eye protection during application.

Response: If irritation occurs or if you feel unwell, get medical attention immediately.

Caution: Disturbing lead paint creates hazardous dust that is harmful to children, pregnant women and workers.

#### STORAGE & DISPOSAL:

Store in a cool, well-ventilated area. Do not dispose in water drains. Contain and collect spillage immediately and dispose of in accordance with government regulations.



Premium Odorless Elastomeric Paint

## YOUR GUARD FOR ANY WEATHER



























Colors may slightly vary from the actual color chips shown.