

ALL PURPOSE - FLEXIBLE  
**WEATHERGARD**

Premium Odorless **Elastomeric** Paint

# ALKALI RESISTANT CONCRETE SEALER (WHITE)



**WEATHERGARD ODOURLESS WATER-BASED ELASTOMERIC ALKALI RESISTANT CONCRETE SEALER WHITE** is lead free high performance primer-sealer based on special acrylic emulsion polymer designed for high alkaline concrete and fresh green new concrete surfaces for a tougher and durable finish. It provides outstanding water, alkali and efflorescence resistance properties where it blocks water penetration and salt migration into the concrete surface. Completely seals surface to prevent paint defects and promote good adhesion. It is easy to use, especially made for rush painting jobs. No Concrete Neutralizer needed as preparation. It can be used for both the interior and exterior application on all new or old concrete surfaces, plaster, masonry and cement walls where the presence of alkali and efflorescence are prevalent.

## PHYSICAL PROPERTIES

<b>GRIND</b>	6 - 7 NS
<b>VISCOSITY</b>	105 - 110 KU @ 28°C
<b>DENSITY</b>	1.12 ± 0.02 kg/liter (Theoretical)
<b>% NON VOLATILE</b>	By Weight 54.69%
<b>(THEORETICAL)</b>	By Volume 38.79%
<b>pH</b>	9 - 9.5

## TECHNICAL INFORMATION

<b>APPLICATION</b>	1 - 2 coats by brush, roller or spray
<b>THEORETICAL COVERAGE</b>	7.70 m <sup>2</sup> /liter @ 50 microns dry film thickness
<b>DRYING TIME</b>	Dries in ½ hour and maybe re-coated in 2 - 4 hours depending on weather condition

## SURFACE PREPARATION

For maximum performance, surfaces to be painted must be dry and in sound condition, free from lost dirt, dust, oil, grease and other foreign matter.



- Elastomeric “Green” Sealer for newly cured concrete
- No concrete neutralizer required
- Blocks water penetration and salt migration into the concrete surface
- For very rush painting works



### WARNING

#### HAZARD STATEMENTS:

Causes skin and serious eye irritation.  
May cause respiratory irritation.

#### PRECAUTIONARY MEASURES:

Keep container tightly closed. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in well ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Dispose of contents/containers in accordance with local, regional, national and international regulations.



**Sycwin Coating & Wires, Inc.**

93 Joy St., Grace Village, Balingasa, Quezon City 1115 Philippines  
Tel: (632) 8364-6001 to 06; 8364-5790; 3411-3491 to 93 • Fax: (632) 8364-3870  
Email address: sales@sycwin.com • Web: www.sycwin.com  
Like us at [www.facebook.com/sycwinpaints](https://www.facebook.com/sycwinpaints)